



Self-Leveling Dispensers for Cups, Saucers, Glasses, & Bowls Cantilever style




CM-1020-C




CM-2020-C




CM-2620-C-10




CM-2620-C-20



CM-2720-C-10



CM-2720-C-20


Capacities and Dimensions**

Model	Cups	Glasses	Bowls	Saucers	Length	Width	Height
CM-1020-C	70	95	72	-----	23 1/2"	19 5/8"	35 1/2"
CM-2020-C	140	190	144	-----	23 1/2"	29 5/8"	35 1/2"
CM-2620-C-10	140	-----	-----	140	23 1/2"	36 1/4"	35 1/2"
CM-2620-C-20	140	-----	-----	140	23 1/2"	36 1/4"	35 1/2"
CM-2720-C-10	140	-----	-----	210	23 1/2"	46 3/4"	35 1/2"
CM-2720-C-20	140	-----	-----	210	23 1/2"	46 3/4"	35 1/2"

* Height excludes flange & guide posts. Add 3-1/4" for overall height.
** Actual capacities vary with shape of object to be dispensed.

-10 models hold
up to 5-3/4" dia. plates

-20 models hold
5-7/8 to 7-1/4" dia. plates

General Specifications

Caddy Magic self-leveling dispenser to be Caddy Corporation model CM-_____.

Self-leveling mechanism to be cantilevered suspension type. Removable panel to be provided in the 18 gauge stainless steel upright enclosed mechanism housing, to permit easy calibration without the use of tools, for full load factors from 20 to 182 pounds and without prior identification of wares, irrespective of weight, height, or brand. Mechanism to be free of cables, chains, pulleys, sprockets, gears, levers, crank handles or components requiring periodic maintenance and lubrication.

Removable load platform to be 18 gauge stainless steel and secured to 16 gauge stainless steel angle support frame and a pair of cantilevered suspension arms. Suspension arms to be of rust-resistant 1/4" steel and to be securely guided by ball bearing rollers. Total stacking height to top of housing to be not less than 22".

The lower rack storage platform to be formed of 16 gauge stainless steel, channeled down on all four sides with two stainless steel reinforced members underneath. Unit to be mounted on four 4" diameter swivel type casters with polyurethane tires.

Saucer model specifications:

Self-leveling cylinders to be field adjustable without the use of tools for china and plastic saucers without requiring prior identification, irrespective of weight, height, or brand. Calibrating mechanism to have multiple extension springs peripherally suspended from a circular storage bank. Selective engaging of springs with dish carrier assembly to permit balancing and dispensing of any load within range of model selected. Cylinders to have 18 gauge stainless steel raised top flange, in high luster finish, with three 3" high plastic guide posts equally spaced.

Unit to be provided with the following accessories:

Accessories

- ACC-63** - 5" diameter swivel casters with polyurethane tires in lieu of 4" diameter swivel casters. (Add 1-1/8" to height)
- ACC-41** - Caster brakes on two diagonal casters.
- ACC-50** - Perimeter bumpers with replaceable corner bumpers. (Add 1-1/4" to length and width)
- ACC-52** - Vertical corner bumpers only. Easy to replace. (Add 1-1/4" to length and width)

CADDY CORPORATION
509 Sharptown Road P.O. Box 345
Bridgeport, NJ 08014-0345
Tel: 856-467-4222 Fax: 856-467-5511
internet: www.caddycorp.com