



Model: _____ Item #: _____ Date: _____
 Project: _____ Qty: _____ Approved By: _____

Self-Contained Draft Beer Coolers

REFRIGERATION



DB60L-SSS-LR shown

Available in 36", 60", 72", and 84" sizes

OPTIONAL ACCESSORIES

BS-100	Four 6" Stainless Steel Legs
BS-101	Six 6" Stainless Steel Legs (for 72" and 84" models)
BS-102	Four 4" Stainless Steel Legs
BS-103	Six 4" Stainless Steel Legs (for 72" and 84" models)
BS-106	Left Side Stainless Steel Kick Plate
BS-107	Right Side Stainless Steel Kick Plate
BC-130	Four 1" Ultra Low Profile Casters w/ Brakes
BC-131	Six 1" Ultra Low Profile Casters w/ Brakes (for 72" and 84" models)
BC-132	Four 2" Low Profile Casters w/ Brakes
BC-133	Six 2" Low Profile Casters w/ Brakes (for 72" and 84" models)
BC-134	Four 3" Casters with Brakes
BC-135	Six 3" Casters with Brakes (for 72" and 84" models)
BC-136	36" Stainless Steel Front Kick Plate
BC-160	60" Stainless Steel Front Kick Plate
BC-172	72" Stainless Steel Front Kick Plate
BS-184	84" Stainless Steel Front Kick Plate

STANDARD FEATURES

Electrical	115 V, 1 Phase, 60 Hz. Furnished with 8;-0" plug-in cord, which exits left or right rear of cooler. NEMA 5-15P plug configuration. Dedicated 15 Amp circuit recommended. 1 Door (36"): 3.6 Full Load Amps, 1/5 HP 2 Door (60"): 6.0 Full Load Amps, 1/4 HP 2 Door (72"): 6.0 Full Load Amps, 1/4 HP 3 Door (84"): 9.0 Full Load Amps, 1/3 HP															
Refrigeration	Self-contained 134A Refrigerant. 30°F - 40°F operating range. Digital thermostat on front grille. R290 Hydrocarbon refrigerant available.															
Keg Capacity	<table border="1"> <thead> <tr> <th></th> <th>36"</th> <th>60"</th> <th>72"</th> <th>84"</th> </tr> </thead> <tbody> <tr> <td>1/4 Keg</td> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> <tr> <td>1/2 Keg</td> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> </tbody> </table>		36"	60"	72"	84"	1/4 Keg	1	2	3	4	1/2 Keg	1	2	3	4
	36"	60"	72"	84"												
1/4 Keg	1	2	3	4												
1/2 Keg	1	2	3	4												
Interior	20 gauge galvanized walls with coved corners. Removable corrugated stainless steel floor racks. Door opening: 29-11/16"H x 19-15/16"W															
Exterior	Sides: 20 gauge stainless steel Front: 20 gauge stainless steel or black vinyl Back: 20 gauge galvanized steel Top: 1" stainless steel top with 16" x 8" drainer															
Doors	24"W doors with full length stainless steel handles with built-in locks. Heavy duty 18-gauge door jambs.															
Shelves	NSF epoxy coated shelves. One bottom and two adjustable shelves per door.															
Number of Faucets	1 Door (36"): 1 2 Door (60"): 2 2 Door (72"): 3 3 Door (84"): 4 Additional beer tower options available. Up to 8 taps, four sixtels per door.															
Insulation	2" thick foamed-in-place polyurethane															
Plumbing	No drain required. Condensate evaporator pan included 1/2" drain line provided from beer drainer exits bottom front of refrigeration compartment															

This equipment is intended for the storage and display of non-potentially hazardous bottle or canned products only.



CONFORMS TO UL Std 471 & NSF STD 7



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Self-Contained Draft Beer Coolers

REFRIGERATION

