



Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Stem Casters



cart-washable
caster

Cart-Washable Casters

Features stainless steel boot, swivel stem, sealed precision bearings, and polyurethane wheel.

type	stainless steel model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5WPS-300	300	136.1	5"	127	1 1/4"	32	2.0	0.9
brake	CSB5WPS-300	300	136.1	5"	127	1 1/4"	32	2.0	0.9




polymer caster

Polymer Casters

With polyurethane tread.

type	model #	type of bearing	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPSS5-250	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9
brake	CPSB5-250	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9



channel frame

Channel Frames—for Rigid Stem Casters

Please note that shelf width must be known when ordering rigid stem casters in order to ship appropriate channel frame to lock rigid casters.

model #	shelf width		weight	
	in.	mm	lbs.	kg
A201706	14"	356	1.5	0.7
A201007	18"	457	2.0	0.9
A201008	21"	533	2.5	1.1
A201009	24"	610	2.8	1.3
A204795	30"	762	3.5	1.6
A207562	36"	914	4.0	1.8



donut bumper
#A200019

Donut Bumpers—for all Stem Casters

description	model #
3 1/2" (89mm) diameter	A200019
5" (127mm) diameter, with swivel center	A213261

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com • www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC Division: Phone 800-637-5100

Printed in U.S.A.
©2019 by Eagle Group

Rev. 09/19

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.