

ROLL-IN FREEZER

FISA-2D-S1-HC





- **3 Year Parts & Labor Warranty Plus An Additional 4 Year Compressor Warranty** Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (Parts Only)

OPTIONS & ACCESSORIES

- Secure-Temp[™] Technology
- Stainless Steel Back
- Stainless Steel Exterior Floor (base)

CABINET CONSTRUCTION

PROJECT: ____

ITEM # _____

AIA # _____

MODEL # _____

_____ SIS # ___

- Stainless Steel Exterior
- Aluminum Interior
- Heavy-Duty Cam Hinges
- Stay-Open Door Feature For Easy Product Loading
 - Heavy-Duty 20 Gauge Stainless Steel Door
- Heavy-Duty Cylinder Lock
- Steel Interior Door Liner
- Stainless Steel Adjustable Door Wiper Gasket
- One-Piece, Snap-In Magnetic Door Gasket
- Low Profile Vertical Door Handle
- **Hinged Front Shroud**
- Energy Saving Thermal Breaker With Stainless Steel Breaker Caps
- Accepts carts (one per door section) 26 1/2"W x 29"D x 65"H (cart not included)
- 8' Cord and Plug (see electrical data for details)

FEATURES

- Full Electronic Control With Touchpoint Interface
- **Expansion Valve Technology**
- **One Touch Defrost**
- Manager's Lockout Feature
- High Performance, Balanced, Top-Mounted Refrigeration
- Anti-Condensate Door Perimeter Heaters

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More **Consistent Product Temperatures**
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Freezer Capable Of Maintaining Product Temperature -10°F



• Exterior Laminate

· Correctional Facilities Option


3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168 Sales@VictoryRefrigeration.com VictoryRefrigeration.com

• FlexTemp Maintain Between 0°F And• 20°F

Door Swing Orientation (at time of order)

_____ QTY: _





We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

Required	Clearance:	Top 12".	Rear 3".	Sides 0"
rioquirou	olourunoo.	10p 12,	nour o,	01000 0

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft)	70.84	Cabinet Voltage	115/60/1	Height	91″
Width, Overall (in.)	68 7/8″	Total Amperes	13.9	Width	84″
Depth, Overall (with handle)	36 5/8″	NEMA Plug* (8' cord)	5-20P	Depth	48″
Height Overall	84 1/2"	REFRIGERATION DATA		Created Weight	644 lbs
Depth, Door Open 90°	66 1/8"	Condensing Unit Size, HP*	(2) 3/4		0
Door Opening (in.)	27 7/8" x 65 1/2"	Refrigerant*	R-290		
No. Of Doors	2	Capacity (BTU/HR) (100°F/20°F)	Variable Speed Technology		

3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 6/3/20 Printed in U.S.A.

an Ali Group Company

