

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Dra		
Pro		
	1000	

Model #: Item # :

Qty :

Super Deluxe Series

Model : TCBE-36SDR-N6

Chef Bases

Available W/H :

Approval :

Chef Base Refrigerator

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



= FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-600)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Strong body and durable construction Built with heavy duty 16 ga. stainless steel, Chef Base top is manufactured of one-piece reinforced stainless steel to ensure durability.

- Digital temperature display on front panel
- Each drawer accommodates up to 6" deep one (1) full size and three (3) 1/6 size pans (drawer pans not included)

Top is insulated to eliminate heat transfer to the interior of cabinet

Countertops

TCBE-36SDR-N6/48/52SDR-N supports up to 788 pounds of equipment. TCBE-72/82SDR-N supports up to 1,192 pounds of equipment. TCBE-96SDR-N supports up to 1,435 pounds of equipment.

Durable stainless steel drawers

Side mount compressor unit

Compressors positioned on the side of the units makes servicing our units easy. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Refrigerator holds 33°F ~ 38°F for the best in food preservation

Refrigerant ISO9001:2008 Intertek							
Model	Drawers	CU./FT.	Countertop Weight Capacity (lbs.)	HP	AMPS	Crated Weight (lbs.)	$L \ge D \ge H^*$ (inches)
TCBE-36SDR-N6	2	4.98	788	1/5	2.8	229	355/8 x 32 x 201/4

* Height does not include 5" for caster height.

Chef Base Refrigerator

Model : TCBE-36SDR-N6

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	() NEMA 5-15P					
Full Load Amperes	2.8					
Compressor HP	1/5					
Cord Length (ft.)	9					
Refrigerant	R-600a					
DIMENSIONAL DATA						
Ext. Length Overall (in.)	355/8 (905mm)					
Ext. Depth Overall (in.)	32 (815mm)					
Ext. Height Overall (in.)*	201/4 (513mm)					
# of Drawers	2					
Net Capacity (cu. ft.)	4.98					
Net Weight (lbs.)	163					
Gross Weight (lbs.)	229					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Height does not include 5" for caster height.

WARRANTY: 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters standard


OPTIONAL ACCESSORIES

• 6" stainless steel leg: 30221M0600


PLAN VIEW


(unit : inch)

* Each drawer accommodates up to 6" deep full size pans (drawer pans not included)



TOP VIEW





Turbo Air : 800-627-0032 **GK** : 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Turbo air Texaking

Ver.20200424

NATURALØ Refrigerant

(GERMAN

KNIFE

