



PROJECT:	MODEL:	QUANTITY:	ITEM NO:

COOK & HOLD SMOKER OVEN

For Various Size Trays, Pans and Gastro-Norm


COOK AND HOLD SMOKERS "LCH-SK-G2" SERIES

G2 FWE's new generation low temperature cook and hold smoker ovens help cut operating costs and increase food quality

- 1** R85/F15 low volume air circulation, 85% radiant / 15% forced air convection - combining radiant and convection heat allows meats to brown naturally and greatly increases yield and profitability
- 2** Drip tray - installed with a tangent draw off for safely removing hot grease and drippings. Easily separates liquids and solids from the pan with a removable stainless steel filter
- 3** Intuitive, easy to use and kitchen friendly controls with 8 programmable recipe presets that allow for consistent results. Provided with an internal product probe, allowing for options to cook and hold by probe or by time without constant monitoring
- 4** Up to 4 hours of smoking in the "smoke drawer" using wood chips. Flush-mounted smoke drawer is easily accessible for safety and cleanliness - refill chips without removing food. Units shipping within the US will be provided with one sample bag of wood chips
- 5** Exclusive unibody design provides the ultimate menu flexibility with two individually controlled compartments, one plug, in the same small space saving foot print. Field reversible doors are standard for added convenience
- 6** When not being used for cooking, these ovens can be used for holding prepared foods. When used for reheating or holding prepared foods, these ovens reduce drying, shrinkage and flavor loss
- 7** These ovens typically require less energy than a conventional oven, and in most cases, since they are being used overnight, they utilize off-peak electric rates for even greater savings



**Two year limited warranty*



1 Reduce Shrinkage, Natural Browning



2 Drip Tray



3 Control Panel



4 Smoke Drawer




CE IP X4



PROJECT:	MODEL:	QUANTITY:	ITEM NO:
----------	--------	-----------	----------

SPECIFICATIONS: COOK & HOLD SMOKER OVEN



MODEL NUMBER	[A] STANDARD ADJUSTABLE SLIDES: NUMBER OF TRAYS / PANS @ 4.5" Spacings (114mm)										OPTIONAL FIXED RACK: NUMBER OF TRAYS / PANS @ 3" Spacings (76 mm)							OVERALL EXTERIOR DIMENSIONS IN. (mm) (Height Includes Casters)			CLASS 100					
	TRAY/PAN SLIDES PROVIDED	18 x 26	12 x 20	14 x 18	18 x 13	20 x 22	10 x 20	GN 2/1	GN 1/1	21" x 27" Shelf Standard	TRAY/PAN SLIDES PROVIDED	18 x 26	12 x 20	14 x 18	18 x 13	20 x 22	10 x 20	GN 2/1	GN 1/1	21" x 27" Shelf Standard	HIGH "H"	DEEP "D"	WIDE "W"	NUMBER OF DOORS	CASTER SIZE	SHIP WT. LBS. (KG)
	LCH-5-SK-G2	3 pr	3	6	6	6	3	6	3	6	3	5 pr	5	10	10	10	5	10	5	10	3	35" (889)	39" (991)	27.5" (699)	1	5"
LCH-6-SK-G2	4 pr	4	8	8	8	4	8	4	8	4	6 pr	6	12	12	12	6	12	6	12	3	39" (991)	39" (991)	27.5" (699)	1	5"	355 (161)
LCH-6-6-SK-G2 Double Compartment / Split Cavity	8 pr	8	16	16	16	8	16	8	16	6	12 pr	12	24	24	12	24	12	24	6	68" (1727)	39" (991)	27.5" (699)	2 Dutch	5"	605 (274)	

MODEL NUMBER	STANDARD FIXED RACK: NUMBER OF TRAYS / PANS @ 3" Spacings (76 mm)							[A] OPTIONAL ADJUSTABLE SLIDES: NUMBER OF TRAYS / PANS @ 4.5" Spacings (114mm)							HIGH "H"	DEEP "D"	WIDE "W"	NUMBER OF DOORS	CASTER SIZE	SHIP WT. LBS. (KG)						
	TRAY/PAN SLIDES PROVIDED	18 x 26	12 x 20	14 x 18	18 x 13	20 x 22	10 x 20	GN 2/1	GN 1/1	21" x 27" Shelf Standard	TRAY/PAN SLIDES PROVIDED	18 x 26	12 x 20	14 x 18							18 x 13	20 x 22	10 x 20	GN 2/1	GN 1/1	21" x 27" Shelf Standard
LCH-1826-7-SK-G2	7 pr	7	-	14	14	-	-	-	-	3	5 pr	5	5	10	10	-	-	-	5	3	41" (1041)	39" (991)	24.75" (629)	1	5"	340 (155)
LCH-1826-7-7-SK-G2 Double Compartment / Split Cavity	14 pr	14	-	28	28	-	-	-	-	6	10 pr	10	10	20	20	-	-	-	10	6	71.25" (1810)	39" (991)	24.75" (629)	2 Dutch	5"	590 (268)

[A] Uprights punched on 1.5" (38mm) centers. Tray slides are adjustable. [B] Shelves are removable and adjustable. Shelf Size: 21" x 27" (514mm x 686mm). Note: Unit standard with maximum 350°F thermostat. Thermostat maximum temperature can be adjusted in the factory or out in the field to meet your local codes.

Single Phase Models	ELECTRICAL: LCH-5-SK-G2, LCH-6-SK-G2, LCH-1826-7-SK-G2				PLUGS	U.S. & CANADA
	VOLTS	WATTS	HERTZ	AMPS		
	208	2535	60	12.2	U.S. & CANADA 6-20P	
	220-240	3360	50/60	14		U.S. & CANADA 6-15P 6-20P
	230	3013	50/60	13.1		INTERNATIONAL * BS 1363 UK1-13P CEE 7/7 EU1-16P
Three Phase Models	208	2535	60	10.6	U.S. & CANADA 15-15P	
	220-240	3360	60	12.1		U.S. & CANADA 15-15P+ 15-20P

* Additional international plugs available. + Dedicated Circuit

Single Phase Models	ELECTRICAL: LCH-6-6-SK-G2, LCH-1826-7-7-SK-G2				PLUGS	U.S. & CANADA
	VOLTS	WATTS	HERTZ	AMPS		
	208	5070	60	24.4	U.S. & CANADA 6-30P 6-50P	
	220-240	6720	50/60	28		U.S. & CANADA 6-30P 6-50P
	230	6026	50/60	26.2		INTERNATIONAL *
Three Phase Models	208	5070	60	15.4	U.S. & CANADA 15-20P	
	220-240	6720	60	17.7		U.S. & CANADA 15-30P

* Units shipping outside of the U.S. and Canada will be supplied with no plug.

CONSTRUCTION. Heliarc welded, single unit construction of stainless steel; 20 gauge polished exterior, 22 gauge stainless steel interior with easy-to-clean coved corners.
INSULATION. Insulated throughout; top, back, bottom, sides, doors using high density ceramic and fiberglass insulation.
DOOR AND LATCH. Flush mounted, double pan, stainless steel insulated vented door(s). Heavy-duty, die-cast, edgemount, full grip, magnetic door latch with heavy-duty hinges. Door shall be field reversible.
CASTERS. Maintenance free polyurethane tire casters in a configuration of two (2) rigid and two (2) swivel with brake.
ADJUSTABLE SPACINGS. Welded rod-style tray slides are stainless steel for greater durability and sanitation. Fully adjustable/removable and designed to give secure bottom tray support. Removable stainless steel uprights shall be punched on 1.5"

(38mm) spacings for easy tray adjustment, and shall easily lift off of heavy-duty stainless steel brackets without the use of tools for cleaning. Three (3) stainless steel, rod type shelves, provided per cavity. Standard on LCH-5-SK-G2 and LCH-6-SK-G2 and LCH-6-6-SK-G2.
FIXED SPACINGS. Removable pair of one piece stainless steel racks with fixed spacings of 3" between slides. One piece rack is easy to remove without the use of tools for cleaning. Three (3) stainless steel, rod type shelves, provided per cavity. Standard on LCH-1826-7-SK-G2 and LCH-1826-7-7-SK-G2.
HEATING SYSTEM. R85/F15 low volume air circulation produces approximately 85% radiant heat with 15% forced air convection for minimal product shrinkage. Built-in heat system includes multiple Incoloy sheathed heating elements that provide fast heat up and accurate temperature set points to hold mode, maintaining food quality and

safe holding temperatures in either cook or holding periods. Independently controlled single zone 300 Watt insulated smoker element
CONTROL PANEL. Easy to operate, automatic controls include intuitive easy to use / easy to read kitchen friendly controls allows "set-and-forget" consistent results. Cooking by time or by internal product temperature with probe (included) when cook cycle is complete, controller automatically switches from cook cycle to hold cycle. Unit has preset function to store and quickly retrieve up to 8 recipes. Adjustable COOK control up to 200°F (93°C). Shall include ON/OFF switch. Actual cabinet temperature reading is LED displayed during each cycle and probe temp display. Smoke element is adjustable for 1-4 hour smoke through the control interface, and is independently controlled to allow for cold smoking application and smoking while cooking.

DRIP TRAY. Installed with a tangent draw off for safely removing hot grease and drippings. Easily separates liquids and solids from the pan with a removable stainless steel filter.
DRIP PAN. External drip tray removable for easy cleaning.
VENTING. Consult factory if lower temperature is required for local codes.
ELECTRICAL CHARACTERISTICS. 3 wire grounded power cord and plug, rear mounted for safety. See electrical data chart above for amperage and receptacle configuration. See electrical chart for models that require a dedicated circuit. Standard with rear mounted cord winder bracket.
INSTALLATION. Unit should not be installed in an area where adverse environmental conditions are present.

- OPTIONAL ACCESSORIES**
- CASTERS**
 - All swivel or larger casters
 - SPACINGS**
 - Extra tray slides
 - Extra stainless shelves
 - EXTRAS**
 - Menu card holder
 - Top corner bumpers
 - Bottom corner bumpers
 - Extra probe
 - Push pull handles
 - Transport latch
 - Rib rack
 - Bear claws
 - Potato spike
 - Chicken rack
 - Low voltage 120V, 20A service available for models LCH-5-SK-G2 and LCH-6-SK-G2. See specification sheet 06-08
 - Chimney vent



FOOD WARMING EQUIPMENT COMPANY, INC.
 5599 HWY. 31 W. Portland, TN 37148
 800-222-4393 | WWW.FWE.COM | SALES@FWE.COM



FWE products may be covered under one or more of the following U.S. patents: 288,299;238,300;3,952,609;4,192,991. All rights reserved. All specifications subject to change without notice. Errors subject to correction.
 © 19 Food Warming Equipment Company, Inc. | R.19.03