

ob _____



REGULAR ERECTA SHELF® SHELVING ACCESSORIES


• Wall Mounts: Used to create wall-mounted shelving units with 12" or 18" (305 or 460mm) regular Erecta Shelf® shelves of any length. Models are available to accommodate from one to five shelves. Each mount consists of shelf support and mounting brackets. Wall bolts or screws not included; they must be selected according to type of wall. Order shelves from sheet #10.50.

Dimensions:

	idth	Hei	ght		Model No.	Approx Wt. (
(in.)	(mm)	(in.)	(mm)	Capacity	Chrome	(lbs.)	(kg)
12	305	103/4	273	1 shelf	12WB1C	21/2	1
12	305	2013/16	529	1 to 3 shelves	12WB3C	5	2
12	305	3013/16	783	1 to 5 shelves	12WB5C	71/4	31/4
18	460	113/4	298	1 shelf	18WB1C	3	11/2
18	460	215/8	549	1 to 3 shelves	18WB3C	6	23/4
18	460	315/8	803	1 to 5 shelves	18WB5C	81/2	4







		A CALLED TO
1		


	_	helf ngth		erall ngth	_	helf idth	_	/erall /idth		rerall eight	Appı Pkd.	
Model No.	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
12WS12C	24	610	26 1/4	670	12	305	13	330	21	530	181/2	81/2
12WS32C	36	910	38 ¹ / ₄	970	12	305	13	330	21	530	25 ¹ / ₄	111/2
12WS52C	48	1220	50 ¹ / ₄	1275	12	305	13	330	21	530	32	143/4

Kit packaged in one box and UPS shippable.





REGULAR ERECTA SHELF® SHELVING ACCESSORIES



1" (25mm) Ledge)

• 1" (25mm) Shelf Ledges: To prevent items from protruding or falling off shelves, ledges can be installed on the shelf edges.


In many cases a one-inch (25mm) ledge will serve the purpose, while allowing access to the shelf from all sides. When a higher ledge is needed, the fourinch (100mm) size can be used on the back or front of the shelf.

For enclosure of the entire back of a shelving unit, rods and tabs (below) can be attached.

Dimenions:

1" (25mm) Back Ledges

m) Back L	Appi Pkd.		
ngth	Model No.	Per 1/	₂ Doz.
(mm)	Chrome	(lbs.)	(kg)
610	L24N-1C	6	23/4
760	L30N-1C	12	51/2
910	L36N-1C	15	7
1060	L42N-1C	16 ¹ / ₂	7
1220	L48N-1C	21	91/2
1525	L60N-1C	221/2	10
	ngth (mm) 610 760 910 1060 1220	(mm) Chrome 610 L24N-1C 760 L30N-1C 910 L36N-1C 1060 L42N-1C 1220 L48N-1C	App. Pkd. (mm) Chrome (lbs.) 610 L24N-1C 6 760 L30N-1C 12 910 L36N-1C 15 1060 L42N-1C 16 ¹ / ₂ 1220 L48N-1C 21



 Rods & Tabs: Rods hook over wires of top shelf and are attached to each of the other shelves with spring-clip tab. Each rod requires one tab for each shelf except top self. Chrome.

Dimensions:

Rods

Upi	right				Appr	OX.
He	ight	Rod	Length		Pkd. Wt.	
(in.)	(mm)	(in.)	(mm)	Model No.	(lbs.)	(kg)
531/2	1360	52	1320	R52C	1	1/2
631/2	1610	61	1550	R61C	1	1/2
731/2	1870	72	1830	R72C	1 1/ ₄	1/2
881/2	2250	86	2185	R86C	11/2	3/4


Tabs

Rods are shipped with sufficient tabs for a 4-shelf unit. For additional tabs order:

Wire Shelf Tab Model No. 9084Z

REGULAR ERECTA SHELF® SHELVING ACCESSORIES





• 8" (203mm) Shelf Dividers: Shelf dividers enable you to compartmentalize shelves, help keep shelf contents orderly. Because they snap into place, they can be positioned and repositioned to exact size of section needed. All models 8" (203mm) high.

			Appro	
			Pkd.	Wt.
Shelf W	idth N	Model No.	Per 1/2	Doz.
(in.) (n	nm)	Chrome	(lbs.)	(kg)
12 3	05	DD12C	12	51/2
18 4	60	DD18C	131/2	6
24 6	10	DD24C	16 ¹ / ₂	71/2

Rods and tabs can serve a similar purpose when entire unit is to be compartmentalized.

REGULAR ERECTA® SHELF

REGULAR ERECTA SHELF® SHELVING ACCESSORIES





• Shelf Spacers: Where shelves are wanted at spacing other than 5" (127mm) increments, shelf spacers wedge into the upright channels to provide a solid support at the desired level. Spacers are used at outside corners, four per shelf.


Model No.
9988Z
99882





 Corner Brace: When regular Erecta Shelf® units are to be joined at right angles, corner braces link shelf ends of one unit to shelf sides of the other, eliminating one upright and leaving the shelving corner open and fully usable. Two required per shelf. Model No. 9999Z





• **Upright Clamp:** Where regular Erecta Shelf® units are to be joined end-to-end, the upright clamp holds the adjacent uprights securely so that each unit buttresses the other. Model No. 9971Z





• Foot Plate: Replaces the leveling bolt. Used when units are to be bolted to the floor or, without bolts, when a broader foot is desired.

Model No. 9993Z

All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation

For Product Information Call: 1-800-992-1776